



CHEMICAL PRODUCTS - SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

| 1.1. Identifier of the product: | SWO – 873X |
|---------------------------------|--------------------------|
| Alternative names | Chemical family: mixture |
| | |

| 1.2. Identified relevant uses of the | substance or mixture and discouraged applications |
|--------------------------------------|---|
| Intended use | : Demulsifier |
| Method of application | : See the technical data sheet. |

1.3. Details of the supplier of the safety data sheet.

| The name of the company | OILFLUX ™. |
|-------------------------|---------------------------|
| | Street Migdia 37, Level 7 |
| | Girona, Spain. 17002 |
| Emergency | |
| Emergency phone: | +34 695949325 |
| | Oilflux ™ |
| Customer service: | +34 695949325 |
| Fax No: | +34 972215835 |
| | |

SECTION 2. HAZARD(S) IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| Indication of danger | Category | Code | |
|---|-------------|------|--|
| Flammable Liquid | Category 3 | H226 | |
| Skin Irritation | Category 2 | H315 | |
| Serious eye irritation | Category 2A | H319 | |
| Specific target organ toxicity – single exposure | Category 3 | H336 | |
| Aspiration Hazard | Category 1 | H304 | |
| Chronic aquatic toxicity | Category 2 | H411 | |

OILFLUXTM TECHNICAL DEPARTMENT



2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) Hazard pictograms :



Signal word

: WARNING

Dangerous components to be indicated on the label:

Solvent naphtha (petroleum), heavy arom. 1-3-5 trimethylbenzene

| Hazard statements | H226 H315 H319 H336 H304 H411 | Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. |
|--------------------------|--|---|
| Precautionary statements | : Prevention: P301+P310 P303+P361+P3 P304+P340 | IF SWALLOWED: Immediately call a POISON CENTER/ doctor. 353 IF ON SKIN (or hair): Take off immediately all contamined clothing. Rinse skin with water/ shower IF INHALED: Remove person to fresh air and keep comfortable for breathing |
| | P305+P351+P3 | 338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| | P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| | P501 | Dispose of contents/ container to an approved waste disposal plant. |

2.3 Other hazards

Result of PBT and vPvB assessment. PBT: Not applicable. vPvB: Not applicable.

OILFLUXTM TECHNICAL DEPARTMENT



SECTION 3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.2 Mixtures

| | Component | CAS # | % |
|----------------------|---|------------|-----------|
| DDBSA and Deriv | vates | | |
| Skin Corr. 1C, H314; | Eye Dam. 1, H318 Acute Tox. 4, H302; Aquatic Chronic 3, H412 | 85536-14-7 | 1 - 5 % |
| 1-3-5 trimethylbe | enzene | | |
| Flam. Liq. 3, H226 | STOT SE 3, H335; Skin Irrit. 2 H315; Eye Irrit. 2 H319; Aquatic | 108-67-8 | 10 - 20 % |
| Chronic 2, H411 | Asp. Tox. 1, H304. | | |
| Heavy Aromatic | Naphta | | |
| Asp. Tox. 1, H304. | Aquatic.Chronic 2, H411 STOT SE 3, H336 | 64742-94-5 | 30 – 50 % |

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

| If inhaled | : In case of unconsciousness place patient stably in side position for transportation. | |
|---|---|--|
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If symptoms persist, call the doctor. | |
| In case of eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If symptoms persist, call the doctor. | |
| If swallowed | : If swallowed, call a poison control center or doctor immediately. | |
| 4.2. Most important symptoms and effects, both acute and delayed | | |
| Symptoms | : None known. | |
| 4.3. Indication of any immediate medical attention and special treatment needed | | |
| Treatment | : None known. | |

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.



Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

| Specific hazards during fire- fighting | : In case of fire hazardous decomposition products may be produced such as: Carbon oxides |
|---|---|
| | Do not use a solid water stream as it may scatter and spread fire. |
| 5.3. Advice for firefighters | |
| Special protective equipment for Firefighte | r : In the event of fire, wear self-contained breathing apparatus. |
| | |

Further information : Use water spray to cool unopened containers.

> Prevent fire extinguishing water form contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

| Personal precautions | : Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. | |
|---|--|--|
| 6.2. Environmental precaution | | |
| Environmental precautions | : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities. | |
| 6.3. Methods and material for containment and cleaning up | | |
| Methods for cleaning | : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13). | |
| 6.4. Reference to other sections | : None. | |

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling



| Advice on safe handling | Keep away from heat and sources of ignition. Do not use sparking tools. Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. | |
|---|---|--|
| Advice on protection against | : Normal measures for preventive fire protection fire and explosion. | |
| 7.2. Conditions for safe storage, including any incompatibilities | | |
| Requirements for storage areas and containers | : Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. | |
| Advice on common storage | : No special restrictions on storage with other products. | |
| Other data | : Stable under recommended storage conditions. | |
| 7.3 Specific end use(s) | | |
| Specific use(s) | : No data available. | |

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-67-8 (1-3-5 Trimethylbenzene, 10 - 20 %) 64742-94-5 (Heavy Aromatic Naphta, 10 - 20 %)

8.2 Exposure controls

Personal protective equipment

| Eye protection | : Tightly fitting sealed goggles |
|-----------------|----------------------------------|
| Hand protection | : Impervious gloves |

Skin and body protection : Impervious clothing

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

OILFLUX™ TECHNICAL DEPARTMENT



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information basic physical and chemical properties

| Appearance | : Liquid |
|------------------------------|--------------------------------|
| Color | : Clear Yellow to Brown |
| | |
| Odor | : Aromatic |
| Odor threshold | : No data available |
| рН | : 4 - 6 |
| Pour point | : No data available |
| Boiling point | : No data available |
| Decomposition temperature | : No data available |
| Flash Point | : ≥ 60°C |
| Evaporation rate | : No data available. |
| Flammability (solid, gas) | : No data available. |
| Upper explosion limit | : No data available. |
| Lower explosion limit | : No data available. |
| Vapor pressure | : No data available. |
| Relative vapour density | : No data available |
| Density | : 0,9 – 0,95 g/cm ³ |
| Water Solubility | : Insoluble |
| Solubility in other solvents | : No data available. |
| Thermal descomposition | : No data available. |
| Viscosity, dynamic | : Wide Range |
| Viscosity, kinematic | : Wide Range |
| | |

9.2. Other information

No data available.

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity No data available.

10.2. Chemical stability

No data available.

10.3. Possibility of hazardous reactions Hazardous reactions: Stable under recommended storage conditions. (SECTION 7)

10.4. Conditions to avoid

Conditions to avoid: Keep away from heat and sources of ignition.

OILFLUX™ TECHNICAL DEPARTMENT



10.5. Incompatible materials:

Materials to avoid: Strong oxidizing agents.

10.6. Hazardous decomposition products

Hazardous descomposition products: No data available.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Primary irritant effect:

Skin corrosion/irritation

Product: Causes skin irritation.

Serious eye damage/eye irritation Product: Causes serious eye irritation.

Respiratory or skin sensitization <u>Product:</u> May be fatal if swallowed and enters airways.

CMR effect (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

STOT – single exposure

Product: May cause drowsiness or dizziness.

STOT – repeated exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

- **12.1 Aquatic toxicity** : No further relevant information available.
- **12.2 Persistence and degradability** : Not easily biodegradable.
- **12.3 Bioaccumulative potential** : No further relevant information available.
- **12.4 Mobility in soil** : No further relevant information available.
- Ecotoxical effects : Toxic for fish

Recommended environmental indications



Water hazard class 2 (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking waterif even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

mPmB: Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product

: Must not be disposed together with household garbage. Do not allow product to reach sewage system.
The product should not be allowed to enter drains, water courses or the soil.
: Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

14.1 Transport information

Uncleaned Packaging

UN number: 1993

UN proper shipping name SWO-DEMULSIFIER

14.2 United Nations Transport Official Designation:

| | 5 trimethylbenzene.), 3, III, ENVIRONMENTALLY HAZARDOUS. |
|---|--|
| • IATA | FLAMMABLE LIQUID, N.O.S (Solvent naphtha (petroleum), heavy arom. DDBSA and Derivates. 1-3- 5 trimethylbenzene.), 3, III, ENVIRONMENTALLY HAZARDOUS |
| 14.3 Transport hazard class: * ADR, IMDG, IATA | |
| Class: | 3 |
| 14.4 Packing group: *ADR, IMDG, IATA | III |

8 of 9

OILFLUX™ TECHNICAL DEPARTMENT



14.5 Environmental hazardous:

Product contains environmentally hazardous substances: Heavy Aromatic Naphta. DDBSA and derivates. 1-3-5 trimethylbenzene.

14.6 Special precautions for user:

Various hazardous Materials and objects.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

*REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of December 16, 2008 on classification, labeling and packaging of substances and mixtures, and by which they are modified and repeal Directives 67/548 / EEC and 1999/45 / EC and amending Regulation (EC) No 1907/2006. *https://echa.europa.eu/es/information-on-chemicals/cl-inventory-database

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant Phrases

| H226 | Flammable liquid and vapour. |
|------|---|
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H304 | May be fatal if swallowed and enters airways. |
| H411 | Toxic to aquatic life with long lasting effects |

Abbreviations and acronyms:

| DDBSA | Dodecyl benzene sulphonic acid |
|---------|---|
| ADR | Agreement on Dangerous Goods by Road |
| IMDG | International Maritime Code for Dangerous Goods |
| IATA | International Air Transport Association |
| CAS | Chemical Abstracts Service |
| PBT | Persistent, Bioaccumulative and toxic |
| vPvB | very Persistent and very Bioaccumulative |
| STOT SE | Specific target organ toxicity – single exposure. |

OILFLUX CAPITAL SL cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

9 of 9

OILFLUXTM TECHNICAL DEPARTMENT